

1. Product Description

Product description	: SOMAFIX FLEXI SILICONIZED SEALANT is a fast curing, acrylic-based, solvent-free, odorless and paintable adhesive with superior adhesion power.
Product form	: Mixture
Trade name	: SOMAFIX FLEXI SILICONIZED SEALANT
Use of the substance/mixture	: adhesives
Recommended use	: Professional uses Consumer use Industrial use
Type of product	: adhesives

2. Characteristics

Characteristics	: Fast curing Odourless Paintable Solvent-free
-----------------	---

3. Application

- Used for bonding many materials such as wood, ceramic, plaster, brick, metal and tile.
- Perfect for fixing moldings, baseboards, plasterboard, PVC panels and decorative materials.
- Used to repair cracks in interior walls.

4. Application Instructions

- The application surface should be dry and cleaned from dirt, dust and oil.
- Cut off the tip of the cartridge and install the gun.
- Apply the adhesive in strips or dots at 15 cm intervals.
- The materials should be properly fixed and pressed for 10-15 minutes.

5. Technical Specifications (@ 23 °C 50% RH)

Physical state	: Solid
Chemical Basis	: Acrylic (Water Based).
Appearance	: Paste.
Odour	: characteristic
Curing System	: Moisture
Skin Forming Time	: 5 – 20 minutes
Curing Rate	: 4 – 5 mm/day
Complete Curing Time	: 24 h
Density	: 1.12 g/cm ³ ±0,05 @23°C
pH	: 7.5 – 9
Thermal Resistance	: 90 °C
Application Temperature	: 5 → 40 °C

6. Packaging

Packaging	: Original packaging
Colour	: White. Anthracite Gray. Black. Grey. Bronze. Golden Oak.

Cartridge 310 ml

Package 24 pcs/ctn

Cartridge 400 ml

Package 24 pcs/ctn

7. Shelf Life and Storage

Storage conditions : Store in a well-ventilated place. Keep cool.

Storage temperature : 5 → 35 °C

Cartridge 310 ml

18 months (after production date, if stored at room temperature)

Cartridge 400 ml

18 months (after production date, if stored at room temperature)

8. Health and Safety

Additional information : Keep away from children

Adverse physicochemical, human health and environmental effects : To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

Other medical advice or treatment : Treat symptomatically.

Hand protection : Protective gloves

Eye protection : Safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

9. Remarks

Remarks : Not suitable for surfaces constantly exposed to water.

10. Standards and Certificates

No information available

Technical Data Sheet

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable